



FIVE YEAR INSTALLATION GUARANTEE

QMS HyperGrip™ is a BBA HAPAS Type 1 High Friction Surface Treatment comprising of Methacole Resin, a pre-accelerated methyl methacrylate binder used with BPO hardener powder and a graded 1 to 3mm calcined bauxite aggregate.

When used in an appropriate location as defined in the “*Guidelines Document for the Assessment and Certification of High Friction Surfacing for Highways*”, should return a service life of between five and ten years.

Quality Marking Services Limited is a BBA HAPAS Approved Installer of QMS HyperGrip™ and guarantees the installation of the system for five years from the date of installation.

The guarantee covers, delamination from the substrate in full or in part together with aggregate loss exceeding that deemed acceptable within the BBA HAPAS documents within the first five years of its serviceable life.

Cracking within the finished surface is not uncommon within High Friction Surface Treatments and does not always constitute a failure. Cracking can occur to the perimeter or in some cases transversely throughout the treated area through expansion and contraction of the flexible substrate. Provided the QMS HyperGrip™ surface is fully bonded to the substrate, there should be no adverse effect to the performance of the system.

The guarantee offered is for the finished surface course of High Friction Surface Treatment and does not include for the substrate on which QMS HyperGrip™ is installed.

The installation of QMS HyperGrip™ shall be in accordance with the BBA HAPAS Certification and the BBA HAPAS Agreed Method Statement, a copy of which accompanies this document.

July 2016

For further information on QMS HyperGrip™ please visit www.qmarkings.co.uk or telephone 01626 836 777

